



C-009.001S(B-009C)

| REV. | REVISIONS                  | REC.    | DATE | REV. | REVISIONS               | REC. | DATE     |
|------|----------------------------|---------|------|------|-------------------------|------|----------|
| 1    | ADD DIMENSION (G)          | 7.5±0.3 |      | 4    | (F):11.5±0.2->11.5±0.15 |      | 01/12/04 |
| 2    | RELOCATE DIM. (E)          |         |      |      |                         |      |          |
| 3    | CANCEL (B); UPDATE DRAWING |         |      |      |                         |      |          |

|   |           |              |           |        |                 |                |         |                   |   |
|---|-----------|--------------|-----------|--------|-----------------|----------------|---------|-------------------|---|
| DRAWN &<br>DRAFTED BY   | WANG CHEN | TOLERANCES   |           | ANGLE: | TITLE:          |                |         |                   |   |
|   |           | 0<L≤4 ±0.1   | pin pitch | ±1°    | CLIP ER-11/5    |                | UL REC. |                   |   |
| CHECKED &<br>APPROVED BY  | JOHN RONG | 4<L≤16 ±0.2  |           | UNIT:  | MM              | CLIP MATERIAL: |         | PIN TENSION LOAD: |   |
|   |           | 16<L≤63 ±0.3 | ORIGIN:   | DG     | STAINLESS STEEL |                |         |                   |   |
| <b>PIN SHINE INDUSTRIAL CO.,LTD.</b><br>TEL:886-2-22990545 FAX:886-2-22990546 |           |              |           | DATE:  | APR.14 '2003    | DRAWING NO.    | C-011   | REV.              | 4 |